

LUMISTAR

LS-84-AP Rugged Aluminum Portable Data Unit Data Sheet

The Lumistar LS-84-AP Rugged Aluminum Portable Data Unit offers a low cost, high performance COTS solution for a portable quick look ground station. Lumistar LS-25 FM Receivers or LS-25-D2 Down Converters with LS-32 Multi-mode IF Receiver, Bit Synchronizers and Multi-function PCM Decommutators, and LS-71 D/A Converters can be installed in this rugged high quality portable computer and bundled with the Lumistar setup, control, and monitoring software to achieve an



affordable alternative to the often expensive, proprietary architecture products of other suppliers. The flexible design allows the user to define the desired data acquisition card configuration to unique requirements.

The computer is a powerful yet portable system capable of handling processor and memory-intensive applications usually reserved for desktop workstations. It allows the ability to use standard add-on cards in application environments that prohibit the use of regular laptops or less rugged lunchbox style computers. It has features that include removable hard drives, shock absorbing bumpers, a large LCD protected by a shatter resistant glass, NEMA 4/12 compliant keyboard and pointing devices, dual cooling fans – all enclosed in a machined black anodized aluminum chassis.

Key Features:

- High Quality Ruggedized Industrial Portable Computer
- 4 Available PCI slots to accept Lumistar boards
- Excellent board cooling through the use of multiple fans
- Accepts:
 - Lumistar FM or Multi-Mode Receivers
 - Lumistar Bit Synchronizers
 - Lumistar PCM Decommutators
 - Lumistar D/A Converters
 - Lumistar Diversity Combiner
 - Lumistar Dynamic Data Simulators
 - Lumistar Drive Bay Products
- Lumistar LDPS Setup, Control, and Display Software is included

Typical Configuration: LS-84-AP-RBD includes the portable computer, Receiver, Bit Synchronizer, and PCM Decommutator with display, control and monitoring software.

Lumistar, Inc.

2270 Camino Vida Roble Suite L

Carlsbad, CA 92011

PHONE: 760-421-2181

FAX: 760-431-2665

EMAIL: sales@lumistar.net

<http://www.lumi-star.com>

Specifications are subject to change. Please verify the latest specifications at time of order.

11-1-13

LS-84-AP Rugged Aluminum Portable Data Unit

Data Sheet

SPECIFICATIONS:

The following products can be installed in the LS-84-AP resulting in an extremely sophisticated telemetry data monitoring system in a portable computer.

FM Receivers:

- LS-25 Multi-band FM Receiver with up to 12 IF Bandwidths/12 Video Filters

Multi-mode Receivers (for FM, PM, BPSK, QPSK, OQPSK, SOQPSK, AQPSK):

- LS-25-D2 Multi-band Down Converter with LS-32-R Multi-mode IF Receiver With 23 IF Bandwidths,16 Video Filters, bit sync and decom optional

ARTM Receiver

- LS-25-D2 Multi-band Down Converter with LS-58-M Multi-mode Demodulator (for ARTM Tier 0, Tier I, and Tier II)

Diversity Combiner

- LS-33 Dual IF Receiver with Pre&Post-D Diversity Combiner and Multi-mode Demod with bit sync and decom optional

Spectral and Oscilloscope Display

- LS-22-SE Spectral and Oscilloscope Display - up to 3 channels

Bit Synchronizers:

- LS-40-DB Bit Synchronizer Daughterboard
- Bit Synchronizer firmware option in all multi-mode demodulators

Multi-function Decoms:

- LS-50 PCI Multi-function PCM Decom or integral with Multi-mode demodulators
- Decom firmware option in multi-mode demodulators

D/A Converters:

- LS-71-P16 16-Channel or P32 32-Channel D/A Converter

Command Data Simulator with FM Modulator

- LS-70-F Command Data Simulator with FM Modulator Option
- LS-70-M Command Data Simulator with ARTM Multi-mode Modulator Option

Computer Specifications:

With changing technology improvements, minimum configuration as of this date would include:

- Machined hard anodized aluminum chassis with rubber corner bumpers. ATX motherboard. Internal cooling fan. Built-in speaker, machined card stabilizers, Pelican Air Cargo case with wheels, Manual and driver CD
- 108 key keyboard with trackpad
- AGP video card with 256 MB
- Motherboard P4 w/LAN, USB 2.0
- 17" TFT display (Resolution 1280 x 1024) 250 cd/m2
- Pentium 4 CPU: 3.0 GHz with 1MB cache and 800MHz Front Side Bus
- CPU fan for Pentium processor; 2 fans for board cooling
- Memory 2GB RAM
- Power Supply : 460watt, Auto-sensing 110/220; 50/60 Hz
- Removable HDD 200 GB
- DVDRW
- Win XP



Environmental Specifications:

Operating Temperature	5° C to +40° C
Non-Operating Temperature	-20° C to +60° C
Operating Humidity	0 to 95% @ 40° C (Non-condensing)
Non-Operating Humidity	Protect from moisture and contamination

Physical Specifications: Size: 17.2" x 13.4" x 9.3" Weight : 44 Lbs (20 kg) typical