



Lumistar LS-68 Options Checklist

1. **Stream 1 Option (Select ONE)**

- Decom Decom w/ Bit Sync
 Super Simulator
-

2. **Stream 2 Option (Select ONE)**

- Decom Decom w/ Bit Sync
 Super Simulator N/A
-

3. **Stream 3 Option (Select ONE)**

- Decom N/A
-

4. **Chassis Format (Select ONE) ¹**

- Modular (User provided cooling) Modular w/ Desktop Chassis
 1U Rack Mount 12" deep (-R1) Portable Lunchbox
 Portable Lunchbox w/ Battery Portable Lunchbox w/ Cooling
 1U Rack Mount 22" deep (-R1P, Includes Processor)
-

5. **Additional Options (Select ALL that apply)**

- Decom Rate Support Extended to 60 Mbps
 IRIG Time Reader/Generator
 PTP Time Reader
 Advanced Networking
-

6. **Recording Options (Select ALL that apply)**

- 64 GB Data Recording
 Allow Saving Setups Internally
-

7. **TMoIP Software Options (Select ALL that apply)**

- CH10-19 Streaming/Recording
 RCC218-10 Streaming
 RCC218-20 Streaming
-

8. **FEC Options (Select ALL that apply)**

- Viterbi Decoding (Conversion Rate = 1/2, k=7)

Standard Included Options – Bold/Italic

For further options and custom builds please contact sales@lumistar.net

¹ Additional Quantity of Streams available in larger form factors, contact sales for details